

DataPoint Advanced Panel Meter



Application

The general purpose 1/8 DIN single-channel meter is offered in three configurations. Select the meter only for indication, the meter with 2 relays for indication and automation, and the meter with 4-20 mA repeater for signal isolation. With the optional MeterView® PC calibration kit, users can conveniently program or clone meters, save meter profiles, datalog and export data to HTML or TXT file formats.

Features


- Relay alternation and lead lag control optimize pump performance and maintenance
- High intensity LED display is readable in direct sunlight for outdoor applications
- Rugged 1/8 DIN polycarbonate enclosure with splash proof NEMA 4X faceplate
- Compatible with analog, voltage and RTD thermocouple sensor inputs

Specifications

| | |
|--|---|
| Display type : | LED, 4-digit |
| Display units: | Engineering |
| Display output: | 0-9999 |
| Input channel: | (1) 4-20mA / 0-10 VDC |
| Supply voltage: | 90-250 VAC, 50-60 Hz. |
| PC-cal. interface:* | RS232 adaptor w/cable |
| PC-cal. software:* | MeterView (Windows®) |
| Memory: | Non-volatile |
| Sensor supply: | 24 VDC @ 200 mA |
| Repeater output: | LI52: Isolated |
| Contact type: | LI51: (2) SPDT relays |
| Contact rating: | LI51: 750 VA |
| Contact output: | LI51: Selectable NO/NC |
| Contact mode: | LI51: Alarm, latched, pump-altern., lead-lage |
| Operating temp.: | F: -4° to 140° C: -20° to 60° |
| Enclosure type: | 1/8 DIN |
| Enclosure rating: | NEMA 4X (IP65) faceplate |
| Enclosure mat'l.: | Polycarbonate FR |
| Classification: | General purpose |
| * Requires the LI97-1001 MeterView calibration kit | |

Calibration

Your indicator may be configured in less than a minute using the MeterView PC calibration kit. User configuration files are retained for indicator cloning and record keeping. The software also provides a convenient interface for data-logging.



LM92 Shown



LM93 Shown

Part Numbers

- LI05-10001

- LI15-10001
- LI25-10001

LI5 -1001

Configuration (1) (2)

- 0 Meter only
- 1 Meter with 2 relays
- 2 Meter with 4-20 mA repeater

Ordering Notes

- 1) For panel mount installation in a NEMA 4X polycarbonate windowed enclosure, order the LM92-1001 (single meter box) or the LM93-1001 (two meter box).
- 2) Order the LI97-1001 MeterView PC calibration kit to program or clone meters, save meter profiles, datalog and export data to HTML or TXT file formats. Each kit includes (1) PC Windows® based MeterView software CD and (1) RS232-RJ11 adapter with 2m cable.

203 Vest Avenue
Valley Park, MO 63088

Toll Free: (888) SPECTECH
Phone: (636) 537-0202

Fax: (636) 537-1405
E-Mail: sales@spectechind.com